

| | | |
|--|----------|----------|
| | Metric | Imperial |
| Maximum Operating Pressure @ 60°C or 140°F | 2068 kPa | 300 psi |

| FP150 Nominal Size | | 3" | 4" |
|--------------------------------|-------------------|-------|-------|
| Outside Diameter | Metric (mm) | 95 | 122 |
| | Imperial (inches) | 3.75 | 4.80 |
| Inside Diameter | Metric (mm) | 77 | 99 |
| | Imperial (inches) | 3.02 | 3.90 |
| Weight | Metric (kg/m) | 2.6 | 4.0 |
| | Imperial (lbs/ft) | 1.7 | 2.7 |
| Min. Bend Radius (operational) | Metric (m) | 1.8 | 2.1 |
| | Imperial (ft) | 6 | 7 |
| Length / Reel | Metric (m) | 750 | 750 |
| | Imperial (ft) | 2461 | 2461 |
| Reel Diameter | Metric (m) | 3.7 | 3.7 |
| | Imperial (ft) | 12 | 12 |
| Reel Width | Metric (m) | 1.2 | 2.4 |
| | Imperial (ft) | 4 | 8 |
| Reel Weight - Full | Metric (kg) | 2631 | 4128 |
| | Imperial (lbs) | 5800 | 9100 |
| Reel Weight - Empty | Metric (kg) | 680 | 1134 |
| | Imperial (lbs) | 1500 | 2500 |
| Fitting Outside Diameter ** | Metric (mm) | 101.6 | 129.3 |
| | Imperial (inches) | 4.00 | 5.09 |
| Fitting Inside Diameter ** | Metric (mm) | 63.5 | 85.9 |
| | Imperial (inches) | 2.50 | 3.38 |

Flow Coefficients

| | |
|------------------|----------------------------|
| Hazen & Williams | 150 |
| Darcy Weisbach | e=0.000005 ft or 0.0015 mm |
| Manning | 0.009 |

** Fitting dimensions do not include O.D. of flange provided for Flanged End Fittings. Fitting O.D. and I.D. applies to Flanged End, Weld-Neck, and Pipe-to-Pipe Coupling fittings. Product Data is subject to change without notice. Flexpipe is not responsible for variations in data presented.



FLEXPIPE
SYSTEMS

Flexpipe products are protected by US Patents: 6,889,716 and 6,902,205